

NORMPACK CERTIFICATE

Registration number: 056 04 100 4878 40

Valid until: 2026-04-17

-		
	Company / address	Polynova Nissen AB
		Victorshorsovijscon 28 SE 126 20 Ujiscovston
		Vretensborgsvägen 28 SE-126 30 Hägersten
	Trade Name (type and/or art.no)	HDPE FJ00952 - 00900, transparent, for conversion to FCM products of bag, sack, sheet, aprons, gloves,
7	All layers in the material, starting	HDPE. Transparent unprinted, thickness 20 μm or less
ō	with food contact layer	
DESCRIPTION		
	Substances with restrictions / SML	Zn
ES		
	Dual use substances	E470a
	B dui doo substantoos	
	Functional barrier according	No
	_	
	to (EU) No 10/2011	
	Assessed according to:	(EC) No 1935/2004 Framework regulation,
	r issessed decording to.	
		(EU) No 10/2011 Plastics, as amended
1		l de la constante de
	Evelopeter dans das die black auf der b	All food types
	Evaluated and suitable for food	An rood types
	types:	
	Evaluated and suitable for time and	OM2 conditions: Long term storage at room temperature and below including hot fill.
\succ		contractions. Eong terms to tage at room temperature and below metading not mil
L F	temperature:	
BIL	Single use / Repeated use	Single use
Ā		
SUITABILITY		
SI	Other restrictions and	
	specifications	
	Overall Migration	Overall migration has been performed on the whole construction to food simulants
		A:10% Ethanol, B:3% Acetic acid, D2:Veg.oil < 1% unsaponifiable matter.
		A:10% Ethanol, B:3% Acetic acid, D2:Veg.oil < 1% unsaponifiable matter,
		at conditions OMX 10 days 40°C.
		at conditions OMX 10 days 40°C. Results < 10 mg/dm2
	Specific migration	at conditions OMX 10 days 40°C.
	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis.
	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals)
	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis.
	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals)
	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals)
	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals)
	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals)
	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals)
SV	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals)
ONS	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals)
TIONS	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals) at conditions 10 days 60°C.
LATIONS	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals) at conditions 10 days 60°C. Results < SML mg/kg
CULATIONS	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals) at conditions 10 days 60°C.
TCULATIONS	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals) at conditions 10 days 60°C. Results < SML mg/kg
CALCULATIONS	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals) at conditions 10 days 60°C. Results < SML mg/kg
5/ CALCULATIONS	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals) at conditions 10 days 60°C. Results < SML mg/kg
TS / CALCULATIONS		at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals) at conditions 10 days 60°C. Results < SML mg/kg Metals in Annex II of (EU) No 10/2011 < SML
ESTS / CALCULATIONS	Specific migration	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals) at conditions 10 days 60°C. Results < SML mg/kg
TESTS / CALCULATIONS		at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals) at conditions 10 days 60°C. Results < SML mg/kg Metals in Annex II of (EU) No 10/2011 < SML
TESTS / CALCULATIONS	Set off	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals) at conditions 10 days 60°C. Results < SML mg/kg Metals in Annex II of (EU) No 10/2011 < SML Not applicable
TESTS / CALCULATIONS		at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals) at conditions 10 days 60°C. Results < SML mg/kg Metals in Annex II of (EU) No 10/2011 < SML
TESTS/CALCULATIONS	Set off Surface to volume	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals) at conditions 10 days 60°C. Results < SML mg/kg Metals in Annex II of (EU) No 10/2011 < SML Not applicable Surface to volume ratio applied 10 dm2 per kg of food
TESTS / CALCULATIONS	Set off	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals) at conditions 10 days 60°C. Results < SML mg/kg Metals in Annex II of (EU) No 10/2011 < SML Not applicable
TESTS / CALCULATIONS	Set off Surface to volume	at conditions OMX 10 days 40°C. Results < 10 mg/dm2 Specific migration has been performed on the whole construction by analysis. B:3% Acetic acid, (metals) at conditions 10 days 60°C. Results < SML mg/kg Metals in Annex II of (EU) No 10/2011 < SML Not applicable Surface to volume ratio applied 10 dm2 per kg of food

Examined by Normpack's secretariat, ensuring that the above material(s) / product(s) at the time of issue of the certificate is/are consistent with the material specific requirements in the Normpack Norm (see back page of certificate) and that a complete documentation does exist. The processor is responsible for fulfiling all legal requirements. This certificate is valid for two years provided that no changes are made in the composition of the material or in the relevant legal requirements. For verification of validity, contact normpack@ri.se.



THE NORMPACK NORM

amended 2023-08-09

§ 1. Materials and articles in contact with food shall meet the demands of Swedish or EU harmonized regulations, as amended:

Swedish regulations	EU-regulations – all materials	EU-regulations - specific materials
<u>SFS 2006:804</u>	(EC) 1935/2004 (Framework reg)	(EC) 450/2009 (A&I packaging)
<u>SFS 2006:813</u>	(EC) 2023/2006 (GMP)	<u>84/500/EEC (Ceramics)</u>
LIVSFS 2023:5 (Contact with Foods)	(EC) 178/2002 (General Food Law)	2007/42/EC (Cellophane)
	(EC) 1333/2008 (Additives)	<u>93/11/EEC (N-nitrosamine)</u>
	<u>(EC) 1334/2008 (Flavourings)</u>	<u>(EC) 1895/2005 (Epoxi)</u>
		<u>(EU) 10/2011 (Plastic)</u> (EU) 2022/1616 (Recycled plastic) (EU) 2018/213 (Plastic-BPA)

§ 2. For materials not covered by Swedish or EU harmonized food contact material regulation, one of the following regulations should be used:

Warenwet	BfR	FDA
<u>The Dutch Packaging and Food-</u> <u>Utensils Regulation</u> (Warenwet), Netherland	<u>Bundesinstitutes fur</u> <u>Risikobewertung (BfR),</u> Germany, Recommendations on	<u>Code of Federal Regulations.</u> <u>Title 21 Food and Drugs, (FDA),</u> <u>USA §§ 174, 175,</u> <u>176, 177, 178, 180, 181, 182,</u> 184, 186 and 189

- § 3. To ensure correct use, suppliers and purchasers throughout the value chain shall confer about the suitability of the material/article for the intended purpose.
- § 4. The transfer of constituents from the food contact material to food shall be assessed.
 If there is a limit regulating materials/articles, the following alternative methods are suggested to establish whether the material/article meets the demands:
 - a) Worst case calculations
 - b) Migration modelling
 - c) Laboratory measurements

All in the Normpack Norm applicable laws and recommendations shall be applied in their latest updated version when issuing a certificate

Contact: normpack@ri.se www.normpack.se



Verifikat

Transaktion 09222115557515455531

Dokument

Normpack Certificate 056 04 100 4878 40 Huvuddokument 2 sidor *Startades 2024-04-17 15:07:35 CEST (+0200) av Hans Steijer (HS) Färdigställt 2024-04-17 15:08:01 CEST (+0200)*

Signerare

Hans Steijer (HS) RISE Research Institutes of Sweden AB Org. nr 556464-6874 *hans.steijer@ri.se* +46 10 228 44 78

an Stai

Signerade 2024-04-17 15:08:01 CEST (+0200)

Detta verifikat är utfärdat av Scrive. Information i kursiv stil är säkert verifierad av Scrive. Se de dolda bilagorna för mer information/bevis om detta dokument. Använd en PDF-läsare som t ex Adobe Reader som kan visa dolda bilagor för att se bilagorna. Observera att om dokumentet skrivs ut kan inte integriteten i papperskopian bevisas enligt nedan och att en vanlig papperutskrift saknar innehållet i de dolda bilagorna. Den digitala signaturen (elektroniska förseglingen) säkerställer att integriteten av detta dokument, inklusive de dolda bilagorna, kan bevisas matematiskt och oberoende av Scrive. För er bekvämlighet tillhandahåller Scrive även en tjänst för att kontrollera dokumentets integritet automatiskt på: https://scrive.com/verify

